




ORGANISED BY











22-26 April, Hanoi, Vietnam





# A Multi-dimensional Cadastral Topological Data Model: Design and Implementation

Yuan Ding dingyuanhhu@hhu.edu.cn









22-26 April, Hanoi, Vietnam





### What are multi-dimensional cadastral objects?

Type code	Туре	Description	Dimension	
<i>o</i> <sub>1</sub>	v+t	A boundary point embedded in 3D/4D space-time	0	
02	e+t	A boundary line embedded in 3D/4D space-time	1	
<i>o</i> <sub>3</sub>	$v+(t_i, t_j) t_i \neq t_j$	The change of a boundary point in a specified time interval		
<i>o</i> <sub>4</sub>	f+t	A boundary face embedded in 3D/4D space-time		
<i>o</i> <sub>5</sub>	$u^2+t$	2		
<b>0</b> <sub>6</sub>	$e+(t_i, t_j) t_i \neq t_j$	The change of a boundary line in a specified time interval		
<b>0</b> <sub>7</sub>	$u^3+t$	A 3D spatial unit embedded in 4D space-time		
08	$f + (t_i, t_j) t_i \neq t_j$	The change of a boundary face in a specified time interval	3	
09	$u^2 + (t_i, t_j) t_i \neq t_j$	The change of a 2D spatial unit in a specified time interval		
<i>o</i> <sub>10</sub>	$u^3 + (t_i, t_j) t_i \neq t_j$	The change of a 3D spatial unit in a specified time interval	4	










22-26 April, Hanoi, Vietnam

"Geospatial Information for a Smarter Life and Environmental Resilience"



#### What are their topological relations?

Type code	<i>o</i> <sub>1</sub>	<i>o</i> <sub>2</sub>	03	<i>o</i> <sub>4</sub>	<i>o</i> <sub>5</sub>	<b>0</b> <sub>6</sub>	<b>0</b> <sub>7</sub>	08	<b>0</b> 9	<i>o</i> <sub>10</sub>
<i>o</i> <sub>1</sub>	ADJ	IN	IN	IN	IN	IN	IN	IN	IN	IN
02		ADJ	ADJ	IN	IN	IN	IN	IN	IN	IN
03			Ø	Ø	Ø	IN	Ø	IN	IN	IN
04				ADJ	Ø	ADJ	IN	IN	Ø	IN
<i>o</i> <sub>5</sub>					ADJ	ADJ	Ø	Ø	IN	Ø
<i>0</i> <sub>6</sub>						ADJ	Ø	IN	IN	IN
<i>o</i> <sub>7</sub>							ADJ	ADJ	Ø	IN
08								ADJ	Ø	IN
09									ADJ	Ø
<i>o</i> <sub>10</sub>										ADJ











22-26 April, Hanoi, Vietnam

"Geospatial Information for a Smarter Life and Environmental Resilience"



Two common ideas for designing the multi-dimensional cadastral topological data model (MDCTDM)

(1) Record all the adjacency and incidence relations for cadastral objects

(2) Record the adjacency relations and the incidence relations between iD and (i+1)D cadastral objects









22-26 April, Hanoi, Vietnam

"Geospatial Information for a Smarter Life and Environmental Resilience"



#### Three conditions for the ideal MDCTDM

- (1) The time should be modeled as a geometric dimension that is the same as the other three geometric dimensions.
- (2) The topological relation between any two cadastral objects can be obtained without computing the topological relations of other cadastral objects.
- (3) Record the topological relations of as few cadastral objects as possible.










22-26 April, Hanoi, Vietnam





#### Conceptual design of the multidimensional cadastral topological data model(MCTDM)



















22-26 April, Hanoi, Vietnam





#### Represent cadastral objects by generalized maps









THE SCIENCE OF WHERE



22–26 April, Hanoi, Vietnam

"Geospatial Information for a Smarter Life and Environmental Resilience"



#### Realizing generalized maps by object-tuple structures

$$a_0$$
:  $(n_0, e_0, f_0, V_0) \leftrightarrow (n_1, e_0, f_0, V_0)$ 
 $a_1$ :  $(n_0, e_0, f_0, V_0) \leftrightarrow (n_1, e_1, f_0, V_0)$ 
 $a_0$ :  $(n_0, e_0, f_0, V_0) \leftrightarrow (n_1, e_0, f_1, V_0)$ 
 $a_0$ :  $(n_0, e_0, f_0, V_0) \leftrightarrow (n_1, e_0, f_0, V_1)$ 










22-26 April, Hanoi, Vietnam





#### **Physical model of MDCTDM**


















22-26 April, Hanoi, Vietnam





#### **Case Study**













22-26 April, Hanoi, Vietnam





#### **SET TRANSACTION NAME 'InsertBoundaryPoint';**

INSERT ObjectTuple VALUES ( $n_7$ ,  $e_7$ ,  $f_3$ ,  $u_0^3$ , NULL,  $n_0$ ,  $e_1$ ,  $f_0$ , NULL, NULL, ID,

INSERT ObjectTuple VALUES  $(n_7, e_7, f_0, u_0^3, \text{NULL}, n_0, e_0, f_3, u_1^3, \text{NULL}, \text{ID}_{n7})$ 

INSERT ObjectTuple VALUES  $(n_7, e_7, f_0, u_1^3, \text{NULL}, n_0, e_0, f_4, u_0^3, \text{NULL}, \text{ID}_{n7})$ 

INSERT ObjectTuple VALUES  $(n_7, e_7, f_4, u_1^3, \text{NULL}, n_0, e_2, f_0, \text{NULL}, \text{NULL}, \text{ID}_{n7})$ 

INSERT Object Tuple VALUES  $(n_7, e_8, f_3, u_0^3, \text{NULL}, n_1, e_4, f_0, \text{NULL}, \text{NULL}, \text{ID}_{n7})$ 

INSERT ObjectTuple VALUES  $(n_7, e_8, f_0, u_0^3, \text{NULL}, n_1, e_6, f_3, u_1^3, \text{NULL}, \text{ID}_{n7})$ 

INSERT ObjectTuple VALUES  $(n_7, e_8, f_0, u_1^3, \text{NULL}, n_1, e_6, f_4, u_0^3, \text{NULL}, \text{ID}_{n7})$ 

INSERT ObjectTuple VALUES  $(n_7, e_8, f_4, u_1^3, \text{NULL}, n_1, e_5, f_0, \text{NULL}, \text{NULL}, \text{ID}_{n7})$ 

UPDATE ObjectTuple SET CadastralObj1D= $e_7$ , Alpha0D= $n_7$  WHERE CadastralObj1D= $e_3$ 

#### AND CadastralObj0D= $n_0$ ;

UPDATE ObjectTuple SET CadastralObj1D= $e_8$ , Alpha0D= $n_7$  WHERE CadastralObj1D= $e_3$ 

AND CadastralObj $0D = n_1$ ;

UPDATE ObjectTuple SET Alpha1D= $e_7$  WHERE Alpha1D= $e_3$  AND CadastralObj0D= $n_0$ ;

UPDATE ObjectTuple SET Alpha1D=  $e_8$  WHERE Alpha1D=  $e_3$  AND CadastralObj0D=  $n_1$ ;

**COMMIT**;












22-26 April, Hanoi, Vietnam





## Thank You!





